

Fender Stripes Installation

- You fender stripes kit will come in 3 pieces. Two of them in the same size and the third one is wider. So you can select 2 same size fender stripes or one smaller and one bigger fender stripes.
- Mix about 7 – 10 drops of baby shampoo (or window tinting film aid which can be bought at any auto parts store) with 1 quart of water in spray bottle.
- Clean up the area where you about to install the stripes on the fender. Also clean up inside and underneath the fender where the stripes will bend around.
- Do not let the backing paper got wet or it will permanently stick to the vinyl.
- Spray the soapy solution on the area you about to install the stripes
- Wet you hand and peel 1 piece of stripes off the backing paper. Spray some soapy solution on the adhesive side of the vinyl and put it on the fender.
- There is no dimension or angle to apply the fender stripes. Different people got different taste so install them at your liking position (check next page for C5 placements)
- Since it is wet application and make sure to spray as much soapy solution as possible on the first stripe piece, so you have about 5 minutes to adjust the first piece. Put it on, step away, and check out if you like the position and angle. Adjust it to your liking position. Squeeze it down to permanent location.
- If you don't have a squeeze, you can use a towel to wrap around your credit card as a squeeze.
- Wait couple hrs to let the vinyl dried out a bit and start massaging the stripes to bend inside and underneath the fender.

C5 Fender Stripes Placements

- You got 3 pieces fender stripes where 2 pieces are the same width and the 3rd one is wider.
- For 2 smaller pieces, there is one piece longer which got the same length as the wider piece.
- Those longer pieces will be the second piece.
- You will need to install this longer piece first which is 11.25" away from the lamp opening along the fender line.
- The => arrow is showing what side of the stripes facing toward the engine bay. The cutting line of the fender stripes is parallel and stick out 3/16" so you will bend it around the fender after the stripes drying out. Make sure to clean that area and the area underneath the fender wells real clean since the stripes will bend around those areas.
- Install the shorter piece to your liking position next to the longer piece. Many people put 1/2" apart.